



Features

- 304 series stainless steel interior
- 430 series stainless steel exterior
- Self closing door
- Recessed door handle
- 3 plastic coated steel shelves included
- Digital temperature controls with LCD Display
- Automatic defrosting
- 4 casters (two locking)
- Door lock
- Foamed in place polyurethane insulation
- ETL Sanitation Listed

Technical Data

Dimensions

Exterior Dimensions (W x D x H)	29" x 32" x 82.5"
Interior Dimensions (W x D x H)	24.5" x 27" x 60.25"
Net Volume (cu. ft.)	23 cu. ft.
Net Weight	281.6 lbs
Packaging Dimensions (W x D x H)	31.5" x 34.5" x 83.5"

Cooling

Temperature Range	32° - 50° F
Refrigerant	R134a
Maximum Ambient Temperature Rating	100.4° F
Defrosting	Automatic
Temperature Display	Yes
Temperature Controller	Digital
H/P	1/3

Construction

Exterior Material	430 series stainless steel
Interior Material	304 series stainless steel
Insulation Material	Foamed in place polyurethane
Shelf Material	Plastic coated steel
Shelf Load Capacity	176.5 lbs

Electrical

Voltage	120
Amps	7.9
Hz	60
Phase	1

With its durable, 430 series stainless steel exterior and 304 series stainless steel interior, the 1 door reach in refrigerator is strong enough to stand up to the daily demands of your busy restaurant kitchen.

The 1 door reach in refrigerator features a self closing door, and four casters, two of which are locking, which make it easy to move the reach in refrigerator for cleaning and servicing. Digital controls and an LCD readout make it easy to adjust the interior temperature. Three plastic coated wire shelves are included. Adjustable mounting brackets allow you to easily change the shelving configuration, to accommodate larger inventory supplies, or small, prepared garnishes, ingredients, and even desserts.

The reach in refrigerator's bottom mounted, 1/3 hp compressor uses R134a refrigerant and is easily accessible for cleaning and maintenance. Foamed in place polyurethane cell insulation helps maintain interior temperatures. The reach in refrigerator has a temperature range of 32° to 50° Fahrenheit.

The single door reach in refrigerator has a 120V, 7.9 amp, 60 Hz. electrical rating, and is ETL Sanitation Listed and NSF Compliant.

Plan View

