



With its durable, 430 series stainless steel exterior and 304 series stainless steel interior, the double door reach in refrigerator is strong enough to stand up to the daily demands of your busy restaurant kitchen.

The 2 door reach in refrigerator features self closing doors and four casters, two of which are locking, which make it easy to move the reach in refrigerator for cleaning and servicing. Digital controls and an LCD readout make it easy to adjust the interior temperature.

Six plastic coated wire shelves are included. Adjustable mounting brackets allow you to easily change the shelving configuration, to accommodate larger inventory supplies, or small, prepared garnishes, ingredients, and even desserts.

The reach in refrigerator's bottom mounted, 1/2 hp compressor uses R134a refrigerant and is easily accessible for cleaning and maintenance. Foamed in place polyurethane cell insulation helps maintain interior temperatures. The reach in refrigerator has a temperature range of 32° to 50° Fahrenheit.

The double door reach in refrigerator has a 120V, 8.4 amp, 60 Hz. electrical rating, and is ETL Sanitation Listed and NSF Compliant.

Features

- 304 series stainless steel interior
- 430 series stainless steel exterior
- Self closing doors
- Recessed door handles
- 6 plastic coated steel shelves included
- Digital temperature controls with LCD Display
- Automatic defrosting
- 4 casters (two locking)
- Door lock
- Foamed in place polyurethane insulation
- ETL Sanitation Listed

Technical Data

Dimensions

| | |
|----------------------------------|------------------------|
| Exterior Dimensions (W x D x H) | 54" x 32" x 82.5" |
| Interior Dimensions (W x D x H) | 49.5" x 27" x 60.25" |
| Net Volume (cu. ft.) | 46.5 cu. ft. |
| Net Weight | 446.6 lbs |
| Packaging Dimensions (W x D x H) | 56.25" x 34.5" x 83.5" |

Cooling

| | |
|------------------------------------|-------------|
| Temperature Range | 32° - 50° F |
| Refrigerant | R134a |
| Maximum Ambient Temperature Rating | 100.4° F |
| Defrosting | Automatic |
| Temperature Display | Yes |
| Temperature Controller | Digital |
| H/P | 1/2 |

Construction

| | |
|---------------------|------------------------------|
| Exterior Material | 430 series stainless steel |
| Interior Material | 304 series stainless steel |
| Insulation Material | Foamed in place polyurethane |
| Shelf Material | Plastic coated steel |
| Shelf Load Capacity | 176.5 lbs |

Electrical

| | |
|---------|-----|
| Voltage | 120 |
| Amps | 8.4 |
| Hz | 60 |
| Phase | 1 |

Plan View

